

## GENERATOR RANGE **EXPERT 4010 X**

SINGLE PHASE 230 V / 50 Hz GASOLINE

MAX OUTPUT

3.3 kW









powered by



Powered with premium engine, known for its reliability, the EXPERT range is dedicated to all professional user. Rugged, powerful and with a clean design, the EXPERT is the perfect companion for the day-to-day intensive use. Available in 230 V / 50 Hz – single phase, the EXPERT range is available with others voltage, current and frequency, plugs, specific or regional adaptation.

|   |       | EXPERT 4010 X   |
|---|-------|-----------------|
| Туре                                    |       | 1 phase         |
| Voltage regulator                       |       | Capacitor       |
| Maximum AC output                       | kW    | 3.3             |
| Continuous operating power (COP)        | kW    | 2.4             |
| Maximum Amps                            | Α     | 14.3            |
| AC voltage                              | V     | 230             |
| Frequency                               | Hz    | 50              |
| Noise level EEC (LwA)                   | dB(A) | 97              |
| Noise level @ 7 m                       | dB(A) | 72              |
| Engine                                  |       | WORMS EX21      |
| Maximum output                          | HP    | 7               |
| Fuel type                               |       | PETROL RON 95   |
| Fuel tank capacity                      | L     | 3.2             |
| Run Time (@ ¾ of the continuous output) | h     | 3 h             |
| Dimensions L x W x H                    | mm    | 600 x 470 x 415 |
| Packaging dimensions L x W x H          | mm    | 615 x 485 x 445 |
| Net weight                              | kg    | 38.5            |
| Gross weight                            | kg    | 39.5            |
| Reference                               |       | 2V0000011       |

## **STANDARD EQUIPMENT**

✓ OHC, 4-stroke gasoline engine

✓ Recoil starter

Electronic oil sensor security

✓ 2 Single phase socket 10/16 A Schuko 230 V

✓ Sockets protected by thermal circuit breaker

## **EQUIPMENT OPTIONAL**

✓ Wheelbarrow kit 1/180 Monobras

✓ Integrated Wheelbarrow kit (factory option)

✓ AVR: Automatic Voltage Regulation (factory option)

Circuit breaker kit (factory option): 30 mA circuit breaker
 + Copper Ground Rod + box

✓ Maintenance KIT N°2