

GENERATOR RANGE TRISTAR 8510 MTXL27 EX DE N/S

THREE PHASE 400 V / 50 Hz GASOLINE

MAX OUTPUT

9 kVA

ALTERNATOR **REINFORCED**



VERY LONG RUN
TANK













Your tools needs three phase current, Tristar range bring you the solution. Equiped with a gasoline engine, you will find surely the best generator that is made for you.

2V0000044

IR	ISIAF	1 65 10	IALLY	L2/	EV DE	IN/ 2
Туре		3	Phase	1	1 Phase	
Voltage regulator			Co	ompou	ınd	
Maximum output	kW		7.2	/	3.7	
Continuous operating power (COP)	kW		5.0	1	-	
Maximum output	kVA		9	1	-	
Maximum Amps	Α		13	/	16	
AC voltage	V		400	/	230	
Frequency	Hz			50		
Noise power level EEC (LwA)	dB(A)			97		
Noise power level @ 7 m	dB(A)			72		
Engine model			WOF	RMS E	EX40	
Maximum output	HP			14		
Fuel type			PETR	OL R	ON 95	
Fuel tank capacity	L			25		
Autonomy (@ ¾ of the continuous output)	h		1	12 h 2	0	
Dimensions L x I x h	mm		870	x 570 :	x 610	
Packaging dimensions L x W x H	mm		890	x 590 :	x 630	
Net weight	kg			100.5	i	
Gross weight	kg			102.5	j	

TRISTAR 8510 MTXL27 EX DE N/S STANDARD EQUIPMENT

✓ OHC, 4-stroke gasoline engine
✓ Recoil starter
✓ DE: Electric start + Battery
✓ ATS: Automatic Transfer Switch Box
✓ Electronic oil sensor security
✓ Large tank
✓ Fuel gauge
✓ ATS: Mains Failure Automatic Transfer Switch
✓ 1 Single phase socket 10/16 A Schuko 230 V
1 EC Three phase socket 400 V / 16 A
Sockets protected by thermal circuit breaker

EQUIPMENT OPTIONAL

✓ Wheelbarrow kit N/360
✓ AVR (factory option): Automatic Voltage Regulation

Kit interdif (factory option): 30 mA interdifferential kit + Copper Ground Rod + box



Reference