

SINGLE PHASE
230 V / 50 Hz
GASOLINE

3 YEARS
WARRANTY

MAX OUTPUT
2.2 kW

VERY LONG RUN
TANK

SOUND PROOF
70 dB(A) at 7 m



Equipped with the inverter technology, this generator delivers a perfect quality of current, voltage and a very stable frequency which make it possible to use even with the most sensitive devices (computers, electronic equipments...). Equipped with the automatic idling system, the engine speed can be automatically adjusted to the required power which reduces consumption and noise. Transportable and soundproofed, this unit is ideal for all types of users and applications, professional, on site and leisure activities. With its coupling function, you can connect in parallel two ACCESS 2000 i and double the available power. It gives you a more powerful generator avoiding the question of additional weight and dimension increase.

ACCESS 2200 XL

Type		1 phase
Voltage regulator		AVR
Maximum AC output	kW	2.2
Continuous operating power (COP)	kW	2
Maximum Amps	A	9.6
AC voltage	V	230
Frequency	Hz	50
Noise level EEC (LwA)	dB(A)	95
Noise level @ 7 m	dB(A)	70
Engine		WORMS R210
Maximum output	HP	5.4
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	15
Run Time (@ ¼ of the continuous output)	h	12 h
Dimensions L x W x H	mm	593 x 465 x 458
Packaging dimensions L x W x H	mm	610 x 490 x 500
Net weight	kg	41
Gross weight	kg	43.5
Reference		200100000

STANDARD EQUIPMENT

- ✓ 4-stroke OHV gasoline engine
- ✓ Recoil starter
- ✓ Electronic oil sensor security
- ✓ AVR: Automatic voltage regulator
- ✓ 2 Single phase sockets 10/16 A Schuko 230 V
- ✓ Sockets protected by thermal circuit breaker
- ✓ DC 12 V output 8.3 A
- ✓ Voltmeter

OPTIONAL EQUIPMENT

- ✓ Wheelbarrow kit EXLE-ACCESS2200