

GENERATOR RANGE ACCESS 3000i

SINGLE PHASE 230 V / 50 Hz GASOLINE

MAX OUTPUT **3 kW**

LONG RUN **TANK**

SOUND PROOF 71 dB(A) at 7 m

WHEELS & HANDLE INTEGRATED











Equipped with the inverter technology, this generator delivers a perfect quality of current, voltage and a very stable frequency which make it possible to use even with the most sensitive devices (computers, electronic equipments...). Equipped with the automatic idling system, the engine speed can be automatically adjusted to the required power which reduces consumption and noise. Transportable and soundproofed, this unit is ideal for all types of users and applications, professional, on site and leisure activities.

		ACCESS 3000 i
Туре		1 phase
Voltage regulator		INVERTER
Maximum AC output	kW	2
Continuous operating power (COP)	kW	2.8
Maximum Amps	Α	13
AC voltage	V	230
Frequency	Hz	50
Noise level EEC (LwA)	dB(A)	96
Noise level @ 7 m	dB(A)	71
Engine		WORMS R210-i
Maximum output	HP	5.4
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	8.5
Run Time (@ ¾ of the continuous output)	h	6 h
Dimensions L x W x H	mm	605 x 432 x 493
Packaging dimensions L x W x H	mm	630 x 470 x 525
Net weight	kg	37
Gross weight	kg	41.5
Reference		200100005

STANDARD EQUIPMENT

✓ 4-st	troke OHV gasoline engine
✓ Rec	coil starter
✓ Oil	sensor with warning light
✓ Aut	omatic idling system
✓ 2 S	ingle phase socket 10/16 A Schuko 230 V
✓ Soc	ckets protected by thermal circuit breaker
✓ USI	B charger
✓ Cor	mnact integrated wheels kit

OPTIONAL EQUIPMENT

Sound proof canopy

✓ Circuit breaker kit (factory option): 30 mA circuit breaker in Box + Copper Ground Rod

Electronic overload protection with warning light