SINGLE PHASE 230 V / 50 Hz GASOLINE

ACCESS 5500 XL

Generator range

MAX OUTPUT 5.5 kW

VERY LONG
AUTONOMY

WELL **EQUIPPED**









The ACCESS 5500 XL gives you a maximum autonomy with a 25 liters extra-large fuel tank. Equipped as standard with an electronic Automatic Voltage Regulator, AVR, this generator is capable to power all your devices and utilities sensitive to voltage variations. User safety and equipment security is ensured by the differential earth leakage circuit breaker, in addition to the thermal overload protection for the sockets. The fully equipped electric control panel is easily accessible. This generator is ideal for construction site, leisure or emergency generator applications.

Serial equipment

- ✓ 4-stroke gasoline engine
- ✓ Recoil starter
- ✓ Electronic oil sensor security / low oil security lamp
- ✓ 1 Single phase socket 10/16 A Schuko
- ✓ 1 EC Single phase socket 230 V / 32 A
- ✓ Sockets protected by thermal circuit breaker
- ✓ Brushless alternator, 2 poles
- DC 12 V output 8.3 A + Voltmeter
- ✓ AVR: Automatic voltage regulator
- ✓ Earth leakage circuit breaker

Optional equipment

★ Wheelbarrow kit EXLE-ACCESS5500



Male Plug n°2 - 32 A - 230 V

		ACCESS 5500 XL
Туре		1 phase
Voltage regulator		AVR
Maximum AC output	kW	5.5
Continuous operating power (COP)	kW	5
Maximum Amps	A	23.9
AC voltage	V	230
Frequency	Hz	50
Noise power level CEE (LwA)	dB(A)	97
Noise power level @ 7 m	dB(A)	72
Engine		WORMS R390
Maximum output	HP	10.1
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	25
Autonomy (@ ¾ of the continuous output)	h	8 h
Dimensions L x W x H	mm	697 x 554 x 549
Packaging dimensions L x W x H	mm	860 x 590 x 580
Dry weight	kg	89
Gross weight	kg	91

WORMS Entreprises

Z

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE

TEL. +33 (0) 1 64 76 29 50 FAX +33 (0) 1 64 76 29 99 www.wormsentreprises.com