

SINGLE PHASE
230 V / 50 Hz
GASOLINE

3 YEARS
WARRANTY

MAX OUTPUT
5.5 kW



VERY LONG RUN
TANK



SOUND PROOF
72 dB(A) at 7 m



Optional accessory
 Male plug n°2 - 32 A - 230 V



Wheelbarrow kit
 EXLE-ACCESS5500
 Optional

The ACCESS 5500 XL gives you a maximum autonomy with a 25 liters extra-large fuel tank. Equipped as standard with an electronic Automatic Voltage Regulator, AVR, this generator is capable to power all your devices and utilities sensitive to voltage variations. User safety and equipment security is ensured by the differential earth leakage circuit breaker, in addition to the thermal overload protection for the sockets. The fully equipped electric control panel is easily accessible. This generator is ideal for construction site, leisure or emergency generator applications.

ACCESS 5500 XL

Type		1 phase
Voltage regulator		AVR
Maximum AC output	kW	5.5
Continuous operating power (COP)	kW	5
Maximum Amps	A	23.9
AC voltage	V	230
Frequency	Hz	50
Noise level EEC (LwA)	dB(A)	97
Noise level @ 7 m	dB(A)	72
Engine		WORMS R390
Maximum output	HP	10.1
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	25
Run Time (@ ¼ of the continuous output)	h	8 h
Dimensions L x W x H	mm	697 x 554 x 549
Packaging dimensions L x W x H	mm	860 x 590 x 580
Net weight	kg	84
Gross weight	kg	86.5
Reference		200100006

STANDARD EQUIPMENT

- ✓ 4-stroke OHV gasoline engine
- ✓ Recoil starter
- ✓ Electronic oil sensor security
- ✓ AVR: Automatic voltage regulator
- ✓ 1 Single phase socket 10/16 A Schuko 230 V
- ✓ 1 Single phase socket 230 V / 32 A
- ✓ Sockets protected by thermal circuit breaker
- ✓ DC 12 V output 8.3 A
- ✓ Voltmeter
- ✓ Earth leakage kit

OPTIONAL EQUIPMENT

- ✓ Wheelbarrow kit EXLE-ACCESS5500