

GENERATOR RANGE

EXPLORER 4010 XL12

SINGLE PHASE 230 V / 50 Hz GASOLINE

MAX OUTPUT
3.3 kW

VERY LONG RUN TANK















Equipped with a premium engine, known for its reliability and designed for intensive use, the EXPLORER range is dedicated to all professional user. Designed for frequent, heavy-use and longer run times.

		EXPLORER 4010 XL12
Туре		1 phase
Voltage regulator		Capacitor
Maximum AC output	kW	3.3
Continuous operating power (COP)	kW	2.4
Maximum Amps	Α	14.3
AC voltage	V	230
Frequency	Hz	50
Noise level EEC (LwA)	dB(A)	97
Noise level @ 7 m	dB(A)	72
Engine		WORMS EX21
Maximum output	HP	7
Fuel type		PETROL RON 95
Fuel tank capacity	L	14
Autonomy (@ ¾ of the continuous output)	h	11 h 30
Dimensions L x W x H	mm	620 x 480 x 475
Packaging dimensions L x W x H	mm	635 x 495 x 505
Net weight	kg	46
Gross weight	kg	47
Reference		2V0000021

STANDARD EQUIPMENT

✓ OHC, 4-stroke gasoline engine

Recoil starter

✓ Electronic oil sensor security

✓ 2 Single phase sockets 10/16 A Schuko 230 V

✓ Sockets protected by thermal circuit breaker

EQUIPMENT OPTIONAL

✓ Wheelbarrow kit MONOBRAS EXPLORER

✓ AVR: Automatic Voltage Regulation (factory option)

Circuit breaker kit (factory option): 30 mA circuit breaker
 + Copper Ground Rod + box

✓ Maintenance KIT N°2