

SINGLE PHASE

230 V / 50 Hz
DIESEL

MAX OUTPUT
5.15 kW

LONG RUN
TANK

ELECTRIC
START

CURRENT 
ALTERNATIF

ELECTROD DIAM.
5 MM

ELECTROD
RUTILE



GARANTIE
3 ANS



 Fabriqué en France

At the same time generator and welder, with AC welding current. In welder position, you can make welding with alternating welding current.

MIXTE 5000 DXL15 YN DE

Type		1 Phase
Voltage regulator		Capacitor
Maximum output	kW	5.15
Continuous operating power (COP)	kW	4.5
Maximum Amps	A	22.3
AC voltage	V	230
Frequency	Hz	50
Noise power level EEC (LwA)	dB(A)	103
Noise power level @ 7 m	dB(A)	78
Maximum electrode diameter	mm	Ø 4
Welding Amp Range	A	60 → 180
Striking Alternative Current	V	50 - 62.5
Minimum welding voltage	V	22.4
Maximum Welding Current	A	180
Engine model		YANMAR L100V5
Maximum output	HP	8.4
Fuel type		Diesel
Fuel tank capacity	L	15
Run Time (@ ¾ of the continuous output)	h	9 h 45
Dimensions L x l x h	mm	875 x 535 x 635
Packaging dimensions L x W x H	mm	895 x 555 x 655
Net weight	kg	109
Gross weight	kg	111
Référence		2V0003003

STANDARD EQUIPMENT

- ✓ 4-stroke OHC gasoline engine
- ✓ Recoil starter
- ✓ DE: Electric start + Battery
- ✓ Electronic oil sensor security
- ✓ 2 Single phase socket 10/16 A Schuko 230 V
- ✓ Sockets protected by thermal circuit breaker
- ✓ Intensity rheostat
- ✓ Electric source selector
- ✓ Welding terminals

OPTIONAL EQUIPMENT

- ✓ Wheelbarrow kit N/360 AXE
- ✓ Welding kit: CABLE KIT N° 1
- ✓ Kit interdif (factory option): 30 mA interdifferential kit + Copper Ground Rod + box