

**SINGLE PHASE**  
**230 V / 50 Hz**  
**GASOLINE**

**MAX OUTPUT**  
**7 kW**

**CURRENT ~**  
**AC WELDING**

**ELECTROD DIAM.**  
**5 MM**

**ELECTROD**  
**RUTILE**



**3 YEARS**  
**WARRANTY**



At the same time generator and welder, with AC welding current. In welder position, you can make welding with alternating welding current.

## MIXTE 7000 EX

|   |       |                      |
|---|-------|----------------------|
| Type                                    |       | 1 Phase              |
| Voltage regulator                       |       | Capacitor            |
| Maximum output                          | kW    | 7                    |
| Continuous operating power (COP)        | kW    | 5                    |
| Maximum Amps                            | A     | 21.7                 |
| AC voltage                              | V     | 230                  |
| Frequency                               | Hz    | 50                   |
| Noise power level EEC (LwA)             | dB(A) | 97                   |
| Noise power level @ 7 m                 | dB(A) | 72                   |
| Maximum electrode diameter              | mm    | Ø 5                  |
| Welding Amp Range                       | A     | 60 → 200             |
| Striking Alternative Current            | V     | 45 - 60              |
| Minimum welding voltage                 | V     | 22.4                 |
| Maximum Welding Current                 | A     | 200                  |
| Engine model                            |       | WORMS EX40           |
| Maximum output                          | HP    | 14                   |
| Fuel type                               |       | UNLEADED GASOLINE 95 |
| Fuel tank capacity                      | L     | 6.8                  |
| Run Time (@ ¾ of the continuous output) | h     | 2 h 10               |
| Dimensions L x l x h                    | mm    | 855 x 555 x 542      |
| Packaging dimensions L x W x H          | mm    | 880 x 575 x 555      |
| Net weight                              | kg    | 90.5                 |
| Gross weight                            | kg    | 92                   |
| Reference                               |       | 2V0003001            |

### STANDARD EQUIPMENT

- ✓ 4-stroke OHC gasoline engine
- ✓ Recoil starter
- ✓ Electronic oil sensor security
- ✓ 2 Single phase socket 10/16 A Schuko 230 V
- ✓ Sockets protected by thermal circuit breaker
- ✓ AVR: Automatic Voltage Regulation
- ✓ Intensity rheostat
- ✓ Electric source selector
- ✓ Welding terminals

### OPTIONAL EQUIPMENT

- ✓ Wheelbarrow kit N/360
- ✓ DE: Electric start + Battery
- ✓ Welding kit: CABLE KIT N° 1
- ✓ Kit interdif (factory option): 30 mA interdifferential kit + Copper Ground Rod + box