

**SINGLE PHASE**  
**230 V / 50 Hz**  
**DIESEL**

MAX OUTPUT  
**11.2 kW**

VERY LONG RUN  
**TANK**

ELECTRIC  
**START**

**3000 RPM**



powered by  
**YANMAR**

Ce modèle destiné aux zones résidentielles ou chantiers se distingue par sa compacité et robustesse. Une motorisation Yanmar éprouvée et un alternateur de haute qualité assurent une production d'énergie électrique fiable y compris dans les conditions les plus exigeantes.

## SILENTSTAR 13000D M AVR YN

Type		1 phase
Voltage regulator		AVR
Maximum output	kW	11.2
Continuous operating power (COP)	kW	10
Maximum Amps	A	48.7
AC voltage	V	230
Frequency	Hz	50
Noise power level EEC (LwA)	dB(A)	95
Noise power level @ 7 m	dB(A)	70
Engine model		YANMAR 3TNM72-HWG
Maximum output	ch	19.2
Fuel type		Diesel (Do not use domestic or heating oil)
Fuel tank capacity	L	40
Run Time (@ ¾ of the continuous output)	h	13 h 50
Dimensions L x l x h	mm	1360 x 650 x 840
Packaging dimensions L x W x H	mm	1380 x 650 x 860
Net weight	kg	393
Gross weight	kg	418
Reference		2V0011002

### STANDARD EQUIPMENT

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- ✓ AVR: Automatic Voltage Regulation
- ✓ Starting and Control Module: Voltage, Frequency, Voltmeter
- ✓ Emergency stop button
- ✓ Current leakage protection and circuit breaker
- ✓ Connection for additional options
- ✓ 1 Single phase socket 10/16 A Schuko 230 V
- ✓ 1 EC Single phase socket 230 V / 16 A
- ✓ 1 EC Single phase socket 230 V / 32 A
- ✓ Sockets protected by thermal circuit breaker
- ✓ Sound proof canopy - double layer panel

### OPTIONAL EQUIPMENT

- ✓ Wheelbarrow SILE7-13BRTEG
- ✓ Remote start
- ✓ ATS: Mains Failure Automatic Transfer Switch
- ✓ Clock (factory option)
- ✓ Road trailer (factory option)