SILENTSTAR 6000D M YN

Generator range

MAX OUTPUT 5.2 kW

VERY LONG
AUTONOMY

STARTING ELECTRIC







powered by **YANMAR**

3000 RPM

These models are designed for residential or construction areas and are characterized by their compactness and robustness. A proven Yanmar engine and a high-quality alternator ensure reliable electrical power production even under the most demanding conditions.

Standard Equipment

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- Starting and Control Module: Voltage, Frequencymeter, Voltmeter
- Emergency stop button
- Current leakage protection and circuit breaker

- Connection for additional options
- ✓ 1 Single phase socket 10/16 A Schuko
- ✓ 1 EC Single phase socket 230 V / 16 A
- ✓ 1 EC Single phase socket 230 V / 32 A
- T EG Siligle pilase socket 230 V / 32 F
- ✓ Sockets protected by thermal circuit breaker
- ✓ Sound proof canopy double layer panel

Optional Equipment

- → Wheelbarrow kit: SILE6BRTE
- + Remote start
- + ATS: Mains Failure Automatic Transfer Switch
- + AVR (factory option): Automatic voltage regulator
- ♣ Road trailer (factory option)

		SILENTSTAR 6000D M YN
Туре		1 phase
Voltage regulator		Capacitor
Maximum output	kW	5.2
Continuous operationg power (COP)	kW	4.4
Maximum Amps	А	22.6
AC voltage	V	230
Frequency	Hz	50
Noise power level CEE (LwA)	dB(A)	97
Noise power level @ 7 m	dB(A)	72
Engine model		YANMAR L100V5
Maximum output	HP	8.8
Fuel type		Diesel (Do not use domestic or heating oil)
Fuel tank capacity	L	22
Autonomy (¾ of the continuous output)	h	14 h 20
Dimensions L x I x H	mm	860 x 560 x 720
Packaging dimensions L x W x H	mm	1130 x 630 x 930
Net Weight	kg	170
Gross weight	kg	175

WORMS Entreprises

ZAC de Lamirault 39 rue de Lamirault 77090 Collégien FRANCE

TEL. +33 (0) 1 64 76 29 50 FAX +33 (0) 1 64 76 29 99 www.wormsentreprises.com