

SINGLE PHASE
230 V / 50 Hz
DIESEL

MAX OUTPUT
6 kW

VERY LONG RUN
TANK

ELECTRIC
START

1500 RPM



Optional accessory
Male plug n°2 - 32 A - 230 V

powered by
YANMAR

These models are designed for residential or construction areas and are characterized by their compactness and robustness. A proven Yanmar engine and a high-quality alternator ensure reliable electrical power production even under the most demanding conditions.

SILENTSTAR 7 M AVR YN

Type		1 phase
Voltage regulator		AVR
Maximum output	kW	6
Continuous operating power (COP)	kW	5.5
Maximum Amps	A	23.9
AC voltage	V	230
Frequency	Hz	50
Noise power level EEC (LwA)	dB(A)	86
Noise power level @ 7 m	dB(A)	61
Engine model		YANMAR 3TNM72-GWG
Maximum output	ch	9.8
Fuel type		Diesel (Do not use domestic or heating oil)
Fuel tank capacity	L	40
Run Time (@ ¾ of the continuous output)	h	30 h 30
Dimensions L x l x h	mm	1360 x 650 x 840
Packaging dimensions L x W x H	mm	1380 x 650 x 860
Net weight	kg	396
Gross weight	kg	420
Reference		2V0001001

STANDARD EQUIPMENT

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- ✓ AVR: Automatic Voltage Regulation
- ✓ Starting and Control Module: Voltage, Freqüencymeter, Voltmeter
- ✓ Emergency stop button
- ✓ Current leakage protection and circuit breaker
- ✓ Connection for additional options
- ✓ 1 Single phase socket 10/16 A Schuko 230 V
- ✓ 1 EC Single phase socket 230 V / 16 A
- ✓ 1 EC Single phase socket 230 V / 32 A
- ✓ Sockets protected by thermal circuit breaker
- ✓ Sound proof canopy - double layer panel

OPTIONAL EQUIPMENT

- ✓ Wheelbarrow SILE7-13BRTEG
- ✓ Remote start
- ✓ ATS: Mains Failure Automatic Transfer Switch
- ✓ Clock (factory option)
- ✓ Road trailer (factory option)