

THREE PHASE
400 V / 50 Hz
DIESEL

MAX OUTPUT
7.6 kVA

VERY LONG RUN
TANK

ELECTRIC
START

1500 RPM



powered by
YANMAR

These models are designed for residential or construction areas and are characterized by their compactness and robustness. A proven Yanmar engine and a high-quality alternator ensure reliable electrical power production even under the most demanding conditions.

SILENTSTAR 7 T AVR YN

Type		3 phase	/	1 phase
Voltage regulator		AVR		
Maximum output	kW	6.1	/	2.0
Continuous operating power (COP)	kW	5.5	/	–
Maximum output	kVA	7.6	/	–
Maximum Amps	A	11	/	–
AC voltage	V	400	/	230
Frequency	Hz	50		
Noise power level EEC (LwA)	dB(A)	86		
Noise power level @ 7 m	dB(A)	61		
Engine model		YANMAR 3TNM72-GWG		
Maximum output	ch	9.8		
Fuel type		Diesel (Do not use domestic or heating oil)		
Fuel tank capacity	L	40		
Run Time (@ ¾ of the continuous output)	h	30 h 30		
Dimensions L x l x h	mm	1360 x 650 x 840		
Packaging dimensions L x W x H	mm	1380 x 650 x 860		
Net weight	kg	396		
Gross weight	kg	420		
Reference		2V0001004		

STANDARD EQUIPMENT

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- ✓ AVR: Automatic Voltage Regulation
- ✓ Starting and Control Module: Voltage, Frequncymeter, Voltmeter
- ✓ Emergency stop button
- ✓ Current leakage protection and circuit breaker
- ✓ Connection for additional options
- ✓ 1 Single phase socket 10/16 A Schuko 230 V
- ✓ 1 EC Single phase socket 230 V / 16 A
- ✓ 1 EC Three phase socket 400 V / 16 A
- ✓ Sockets protected by thermal circuit breaker
- ✓ Sound proof canopy - double layer panel

OPTIONAL EQUIPMENT

- ✓ Wheelbarrow SILE7-13BRTEG
- ✓ Remote start
- ✓ ATS: Mains Failure Automatic Transfer Switch
- ✓ Clock (factory option)
- ✓ Road trailer (factory option)