

FRESH WATER

ACCESS J 60-75

Pumps Range

Self-Priming

ENGINE
4ST | Gasoline

DISCHARGE FLOW
60 m³/h

PRESSURE
2.8 bar

SOLID SIZE Ø
6 mm

NET WEIGHT
25 kg



3 YEARS
WARRANTY

The ACCESS models have a 4-stroke engine selected by IMER and are ideally suited for watering and irrigation of parks and gardens as well as emptying the cellar waters.

Standard equipment

- ✓ Four-stroke OHV engine
- ✓ Recoil start
- ✓ Self-Priming
- ✓ Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

Optional equipment

- + Firefighter hose coupling

ACCESS J 60-75

Pump type		Self-Priming
Suction Ø coupling	mm	75 (3")
Delivery Ø coupling	mm	75 (3")
Discharge flow	L/min	1000
Discharge flow	m ³ /h	60
Pressure	bar	2.8
Total dynamic head	m	28
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	6
Mechanical seal		Ceramic carbon
Engine model		WORMS R210
Engine type		OHV, 4-stroke gasoline
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	3.6
Autonomy	h	1 h 30
Dimensions L x l x H	mm	500 x 395 x 445
Packaging dimensions L x W x H	mm	520 x 425 x 455
Net Weight	kg	25
Gross weight	kg	27

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL. +33 (0) 1 64 76 29 50
FAX +33 (0) 1 64 76 29 99
www.wormsentreprises.com