Édition : 20250619

PUMPS RANGE JARD 120HV

CLEAR WATER

Self-Priming

4ST Petrol



DISCHARGE FLOW

7.5 m³/h

PRESSURE 3.5 bar


SOLID SIZE Ø 5.5 mm

NET WEIGHT

15.5 kg



powered by



The JARD models are compact and have a 4-stroke engine, more efficient and more environmentally friendly than 2-stroke engines. Equipped with a carrying handle for easier handling, they are perfectly intended for watering and irrigation of parks and gardens as well as emptying the waters of the cellar.

| | | JARD 12 OHV |
|------------------------------------|-------|------------------------|
| Pump type | | Self-Priming |
| Suction Ø coupling | mm | 25 (1") |
| Delivery Ø coupling | mm | 25 (1") |
| Discharge flow | L/min | 125 |
| Discharge flow | m³/h | 7.5 |
| Pressure | bar | 3.5 |
| Total dynamic head | m | 35 |
| Discharge head | m | 8 |
| Solid size Ø (Ø of strainer holes) | mm | 5.5 |
| Mechanical seal | | Ceramic carbon |
| Engine model | | CC ROBIN EH09 |
| Engine type | | OHV, 4-stroke gasoline |
| Fuel type | | Petrol RON 95 |
| Fuel tank capacity | L | 1.5 |
| Run Time | | 2 h 55 |
| Dimensions L x W x H | mm | 370 x 300 x 420 |
| Packaging dimensions L x W x H | mm | 430 x 340 x 470 |
| Net Weight (Gross weight) | kg | 15.5 |
| Poids brut emballé | kg | 17.5 |
| Reference | | 200004002 |

STANDARD EQUIPMENTS

- ✓ OHV, 4-stroke gasoline engine
- Recoil starter
- Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

OPTIONAL EQUIPMENTS

✓ Firefighter hose coupling