

High Pressure

JET 100 DXL13 DE

Pumps range

Self-Priming

ENGINE
4ST Diesel

DISCHARGE FLOW
27 m³/h

PRESSURE
9 bar

SOLID SIZE Ø
2.5 mm

NET WEIGHT
98 kg



DISCHARGE OUTPUT
3 Way

powered by
YANMAR

Our high-pressure construction pumps effectively move water over long distances or to great heights. They feature large-diameter impellers with shallow vanes for greater pressures and discharge heights, which allows the pumps to move water farther. They are ideal for sprinklers, moving water uphill, handling fast seepage or light firefighting while waiting for emergency crews to arrive.

Standard equipment

- ✓ Four-stroke Diesel engine
- ✓ Recoil start
- ✓ Electric start + Battery
- ✓ 3 way discharge output
- ✓ Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

Optional equipment

- + Wheelbarrow kit
- + Firefighter hose coupling
- + Fire lance with stopcock
- + Wrench for firefighter hose coupling
- + Firefighter delivery hose (20 m) + Suction hose (5 m)

JET 100 DXL13 DE

Pump type		Self-Priming
Suction Ø coupling	mm	50 (2")
Delivery Ø coupling	mm	25/25/40 (1"/1"/1.5")
Discharge flow	L/min	450
Discharge flow	m ³ /h	27
Pressure	bar	9
Total dynamic head	m	90
Discharge head	m	7
Solid size Ø (Ø of strainer holes)	mm	2.5
Mechanical seal		Ceramic carbon
Engine model		YANMAR L100
Engine type		4-stroke Diesel
Fuel type		Diesel (do not use domestic or heating oil)
Fuel tank capacity	L	13
Autonomy	h	6 h
Dimensions L x l x H	mm	840 x 603 x 742
Packaging dimensions L x W x H	mm	1200 x 630 x 825
Net Weight	kg	98
Gross weight	kg	102.5

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL. +33 (0) 1 64 76 29 50
FAX +33 (0) 1 64 76 29 99
www.wormsentreprises.com