

Fresh  
Water

**RD 55**  
Pumps range

Self-Priming

ENGINE  
**4ST Diesel**

DISCHARGE FLOW  
**54 m<sup>3</sup>/h**

PRESSURE  
**2.8 bar**

SOLID SIZE Ø  
**6 mm**

NET WEIGHT  
**41 kg**



powered by  
**YANMAR**

RD range are suitable for clear and light trash transfer and accept particles up to 6 mm. High-performance materials such as the ceramic carbon mechanical seal and die-cast aluminum body pump provide excellent reliability and durability.

#### Standard equipment

- ✓ Four-stroke Diesel engine
- ✓ Recoil start
- ✓ Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

#### Optional equipment

- + Wheelbarrow kit
- + Firefighter hose coupling

RD 55		
Pump type		Self-Priming
Suction Ø coupling	mm	75 (3")
Delivery Ø coupling	mm	75 (3")
Discharge flow	L/min	900
Discharge flow	m <sup>3</sup> /h	54
Pressure	bar	2.8
Total dynamic head	m	28
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	6
Mechanical seal		Ceramic carbon
Engine model		YANMAR L48
Engine type		4-stroke Diesel
Fuel type		Diesel (do not use domestic or heating oil)
Fuel tank capacity	L	2.4
Autonomy	h	2 h 30
Dimensions L x l x H	mm	590 x 460 x 500
Packaging dimensions L x W x H	mm	660 x 470 x 510
Net Weight	kg	41
Gross weight	kg	43
Référence		-

**IMER France**  
DIVISION BÂTIMENT

ZI Les Speyres - CS 70500  
38450 VIF - FRANCE  
TEL. (33) 4 76 72 52 69  
Fax (33) 4 76 72 68 92  
mail : batiment@imer.fr  
www.imer.fr

 Made in France

