

Trash
Water

High Discharge Flow

Intensive Work

SWT 150 HZ DXL45

Pumps Range

Self-Priming

ENGINE
4ST Diesel

DISCHARGE FLOW
150 m³/h

PRESSURE
3.2 bar

SOLID SIZE Ø
31 mm

NET WEIGHT
190 kg



ELECTRIC
Start

EASY QUICK CLEAN
out port

powered by
HATZ
DIESEL

Built around durability, our SWT gasoline trash pumps feature a silicon carbide seal and a unique conical cast iron impeller design and a quickclean out port for easy maintenance and long service life. They reduce wear from abrasive materials and can handle solid objects up to 31 mm in diameter. There's even a strainer to ensure nothing bigger gets through.

Standard equipment

- ✓ Four-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Silicon carbide mechanical seal
- ✓ Steel strainer, hose coupling and clamp
- ✓ Wheelbarrow kit

Optional equipment

- + Firefighter hose coupling

SWT 150 HZ DXL45

Pump type		Self-Priming
Suction Ø coupling	mm	100 (4")
Delivery Ø coupling	mm	100 (4")
Discharge flow	L/min	2500
Discharge flow	m ³ /h	150
Pressure	bar	3.2
Total dynamic head	m	32
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	31
Mechanical seal		Carbure de silicium
Engine model		HATZ 1B50
Engine type		4-stroke Diesel
Fuel type		Diesel (do not use domestic or heating oil)
Fuel tank capacity	L	45
Autonomy	h	10 h
Dimensions L x l x H	mm	1180 x 1000 x 960
Packaging dimensions L x W x H	mm	—
Net Weight	kg	190
Gross weight	kg	—

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL. +33 (0) 1 64 76 29 50
FAX +33 (0) 1 64 76 29 99
www.wormsentreprises.com