

Semi Trash Water

TH 45 EX Pumps Range

Self-Priming

ENGINE
4ST | Gasoline

DISCHARGE FLOW
42 m³/h

PRESSURE
2.3 bar

SOLID SIZE Ø
20 mm

NET WEIGHT
26 kg



**3 YEARS
WARRANTY**

powered by



With deeper impeller vanes coupled with a large volute discharge opening, our semi trash pumps can pass murky water that contains small solid objects without clogging the passage. These self-priming construction pumps feature a tough, silicone carbide mechanical seal. Semi-trash pumps are ideal for dewatering on construction and agricultural sites or in rental applications.

Standard equipment

- ✓ Four-stroke OHC engine
- ✓ Recoil start
- ✓ Electronic oil sensor security
- ✓ Silicon carbide mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

Optional equipment

- + Wheelbarrow kit (factory option): REF. 13
- + Firefighter hose coupling
- + Maintenance KIT N°2

TH 45 EX		
Pump type		Self-Priming
Suction Ø coupling	mm	50 (2")
Delivery Ø coupling	mm	50 (2")
Discharge flow	L/min	700
Discharge flow	m³/h	42
Pressure	bar	2.3
Total dynamic head	m	23
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	20
Mechanical seal		Silicon carbide
Engine model		WORMS EX16
Engine type		OHC, 4-stroke gasoline
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	3.2
Autonomy	h	3 h
Dimensions L x l x H	mm	527 x 368 x 417
Packaging dimensions L x W x H	mm	540 x 380 x 440
Net Weight	kg	26
Gross weight	kg	27

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL +33 (0) 1 64 76 29 50
FAX +33 (0) 1 64 76 29 99
www.wormsentreprises.com