# ENTREPRISES

## FRESH WATER

# TP 36 H Pumps Range

**Self-Priming** 

ENGINE 4ST | Gasoline

DISCHARGE FLOW

31.2 m<sup>3</sup>/h

**PRESSURE** 

3.2 bar

SOLID SIZE Ø

5.5 mm

NET WEIGHT

23.5 kg





powered by **HONDA** 

TP range are suitable for clear and light trash transfer and accept particles up to 7.5 mm. High-performance materials such as the ceramic carbon mechanical seal and die-cast aluminum body pump provide excellent reliability and durability.

### Standard equipment

- ✓ Four-stroke OHC engine
- ✓ Recoil start
- ✓ Electronic oil sensor security
- Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

### **Optional equipment**

- + Wheelbarrow kit (factory option): REF. 13
- + Firefighter hose coupling

		TP 36 H
Pump type		Self-Priming
Suction Ø coupling	mm	50 (2")
Delivery Ø coupling	mm	50 (2")
Discharge flow	L/min	520
Discharge flow	m³/h	31.2
Pressure	bar	3.2
Total dynamic head	m	32
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	5.5
Mechanical seal		Ceramic carbon
Engine model		HONDA GX120
Engine type		OHC, 4-stroke gasoline
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	2
Autonomy	h	1 h 55
Dimensions L x I x H	mm	470 x 356 x 347
Packaging dimensions L x W x H	mm	540 x 380 x 430
Net Weight	kg	23.5
Gross weight	kg	25.5

### **WORMS** Entreprises

ZAC de Lamirault 39 rue de Lamirault 77090 Collégien FRANCE

TEL. +33 (0) 1 64 76 29 50 FAX +33 (0) 1 64 76 29 99 www.wormsentreprises.com