

FRESH WATER

TP 65 H Pumps Range

Self-Priming

ENGINE
4ST | Gasoline

DISCHARGE FLOW
60 m³/h

PRESSURE
3.2 bar

SOLID SIZE Ø
7.5 mm

NET WEIGHT
24.5 kg



**3 YEARS
WARRANTY**

powered by
HONDA

TP range are suitable for clear and light trash transfer and accept particles up to 7.5 mm. High-performance materials such as the ceramic carbon mechanical seal and die-cast aluminum body pump provide excellent reliability and durability.

Standard equipment

- ✓ Four-stroke OHC engine
- ✓ Recoil start
- ✓ Electronic oil sensor security
- ✓ Ceramic carbon mechanical seal
- ✓ Plastic strainer, hose coupling and clamp

Optional equipment

- + Wheelbarrow kit (factory option): REF. 13
- + Firefighter hose coupling

TP 65 H		
Pump type		Self-Priming
Suction Ø coupling	mm	75 (3")
Delivery Ø coupling	mm	75 (3")
Discharge flow	L/min	1000
Discharge flow	m³/h	60
Pressure	bar	3.2
Total dynamic head	m	32
Discharge head	m	8
Solid size Ø (Ø of strainer holes)	mm	7.5
Mechanical seal		Ceramic carbon
Engine model		HONDA GX160
Engine type		OHC, 4-stroke gasoline
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	3.1
Autonomy	h	2 h 15
Dimensions L x I x H	mm	527 x 368 x 417
Packaging dimensions L x W x H	mm	540 x 380 x 430
Net Weight	kg	24.5
Gross weight	kg	26.5